

Waterproof Wire to Wire & Wire to Board

The EDAC E-Inline family of waterproof plug and socket connectors provides a reliable interconnect solution in harsh environments. Single or double latch insulator designs insure superior shock and vibration resistance. A variety of styles are available for different wire gauge applications. These utilize simple crimp and poke contacts. Optional contact plugs are available for use when all contact positions are not required. Additional contacts/wires can then be added in the field.



- Rated current from 3 to 10 Amps for use with wire sizes from 28 to 14 AWG
- 560 and 572 series offer double latch solution
- Available in wire-to-wire and wire-to-board options
- True crimp and poke solution
- Internal polarization to prevent mismating
- · Available with wire already installed
- · Waterproof grade IP52 and IP67 certified

www.edac.net in 🛗 📑 📘

























Waterproof Wire to Wire & Wire to Board Connectors

Series	No. of	Pitch	Current	Latch Type	Polarized	Pre-Installed	WP Grade
	Contacts		Rating			Seals	
560	2, 3 and 5	2.5mm	3 amps	Double	Υ	Y	IP67
565	2, 3 and 5	2.5mm	3 amps	Single	Υ	Υ	IP67
566	2, 3, 4 and 6	2.0mm	2 amps	Single	Υ	Y	IP67
567	2, 3, 4, 6 and 9	5.0mm X 5.9mm	8 amps	Single	Υ	N	IP52
568	1	N/A	12 amps	Single	Υ	N	IP52
570	1, 2 and 3	5.8mm	10 amps	Single	Υ	N	IP67
572	1, 2 and 3	5.8mm	10 amps	Double	Υ	N	IP67



Premium Waterproof wire to wire or wire to board solution

Optional Port Plugs allow circuits to be added in the field















